



Muller

10W30 SL/CF

SUPER EXTRA 7000

A new generation of automotive oils based on revolutionary concepts meeting the performance levels required by today's gasoline engines. It is blended with the most advanced additive package, which enables it to give exceptional performance under most severe operating conditions.

APPLICATIONS

This oil is recommended for gasoline and diesel engine passenger and commercial vehicles of every make and type, turbo charged or natural aspirated, which require API SL/CF quality oil. It can also be used for engines where API service category SJ and earlier Categories are recommended.

FEATURES

It provides effective protection against oxidation, wear and corrosion under high temperature operations and remains a stable multi grade. It provides good cold starting and high resistance to sludge, low volatility characteristics. Low oil consumption and fully compatible with the catalytic converters and exhaust emission control equipment.

SPECIFICATION LEVEL

Muller -SL/CF meets and exceeds the requirements of API SL/CF and the performance requirements of most European, Japanese and American car manufacturers. General Motors GM 6094M. Chrysler MS 6395. JASO MA2. Always follow manufacturers' recommendations and specifications for viscosity grade and API service.

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	11.5
Viscosity index	ASTM D2270		142
Pour point	ASTM D6892	°C	-33
Flash Point COC	ASTM D92	°C	220
TBN	ASTM D2896	mg KOH/g	7.5
Apparent Viscosity, cP	ASTM D5293	mPa.s	6000

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.



RAF TECHNOLOGY INDUSTRIES